



INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 17 AUG 2004


WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 11 August 2004

Act 1977
(A. J)


The Patent Office

30 JUL 03 EB26248-1 001038
P01/7700 0.00-0317727.6

1777

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

48410/P708210GB/JG/SAC

2. Patent application number

(The Patent Office will fill in this part)

0317727.6

29 JUL 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

University of Warwick
Gibbet Hill Road
Coventry
CV4 7AL
United Kingdom

4019162001

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Liquid Viscosity Sensor

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

WITHERS & ROGERS
Goldings House
2 Hays Lane
London
SE1 2HW

Patents ADP number (if you know it)

1776001 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

YES

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 6

Claim(s)

Abstract

Drawing (s) 545 *ll*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(*please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date 28 July 2003

W R
WITHERS & ROGERS

12. Name and daytime telephone number of person to contact in the United Kingdom James Gray 01926 336111

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500 505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

1/5




Fig. 1.




Fig. 2.




Fig. 3.

Post Available Copy

2/5




Fig. 4

3/5





Fig. 5

4/5



5/5




Fig. 7




Fig. 8

Liquid Viscosity Sensor

The present invention relates to a liquid viscosity sensor and in particular to a liquid viscosity sensor which utilises an ultrasonic transducer.

5

It is often a requirement to determine the viscosity of a liquid to, for example, ascertain the condition of the liquid. One particular field where viscosity measurement is important is combustion engine lubrication. It will be appreciated that, over time, a combustion engine lubricant becomes contaminated with unburned hydrocarbons, combustion by-products and particulate matter. These contaminants tend to alter the viscosity of the oil which in turn alters the flow rate of the oil.

10

According to the present invention there is provided a liquid viscosity sensor comprising an ultrasonic source, a sampling body and an ultrasonic receiver, the sampling body including a sampling face adapted to contact a sample of liquid, in use, the source being operable to generate a longitudinal ultrasonic wave which follows a path through the body to the sampling face and onwards to the receiver, wherein the body is configured such that the longitudinal wave emanating from the source is transformed into a horizontally polarised shear wave prior to reaching the sampling face, and the horizontally polarised shear wave is re-transformed into a longitudinal wave before reaching the receiver.

15

20

The present invention thus provides a sensor adapted to utilise the interaction of a horizontally polarised shear wave at a liquid solid interface to measure viscosity, while eliminating the need to provide both a source and receiver configured to generate and receive horizontally polarised shear waves.

25

In a preferred embodiment the transformation in the waves occurs at a common feature of the sampling body. The feature may comprise a reflection point of the body. The

common feature may comprise a reflective face of the body. The face may be substantially planar. The face may be defined by a solid to air interface of the body. The sampling face of the body is preferably planar.

- 5 The reflective face is positioned relative to the source such that a longitudinal wave emanating from the source and impinging upon the reflective face is reflected to produce both a reflected longitudinal wave and a reflected horizontally polarised shear wave, the shear wave being horizontally polarised with reference to the reflective face. The sampling face is positioned relative to the reflective face such that the shear wave
10 emanating therefrom is vertically polarised with reference to the sampling face. The sampling face is preferably positioned such that the shear wave emanating from the reflective face impinges upon the sampling face at a relatively shallow angle, with the result that the shear wave is reflected therefrom.
- 15 The body may further comprise a return reflective face adapted to reflect the wave reflected from the sampling face. In one embodiment the return reflective face may reflect the shear wave back among the same path from which it was received. In an alternative embodiment the return reflective face may reflect the shear wave along a different path. In an alternative embodiment the body may be provided with two or
20 more sampling faces.

- The body preferably comprises a material having both a low acoustic impedance and low ultrasonic attenuation. Preferably the material characteristics of the body are uniform. The body may comprise a plastics material such as, for example, cross-linked
25 polystyrene. The body is preferably provided with acoustic absorption means adapted to absorb unwanted ultrasonic waves. The source and receiver may be embodied by separate components. In an alternative embodiment the source and receiver may comprises a single component.

An embodiment of the present invention will now be described with reference to the accompanying drawings in which:

Figure 1 shows a perspective view from above and to one side of a body forming part of the present invention;

5 Figures 2 and 3 show alternative perspective views of the body of figure 1;

Figure 4 shows a diagrammatic view of a portion of the body and an ultrasonic transducer as indicated by arrow A of figure 1 and showing the path of ultrasonic waves generated by the transducer;

10 Figure 5 shows a diagrammatic view of a portion of the body and an ultrasonic transducer as indicated by arrow A of figure 1 and showing the path of reflected ultrasonic waves received by the transducer;

Figure 6 shows an edge view of the body as indicated by arrow B of figure 1;

Figure 7 shows a schematic view of an alternative embodiment of a body according to the present invention; and

15 Figure 8 shows a simplified diagrammatic view of an ultrasonic transducer.

Referring to the figures there is shown a viscosity sensor apparatus generally designated 10 comprising a sampling body 12 and an ultrasonic transducer 14 acoustically coupled to a face 16 thereof. The body 12 is comprised of a block of material having both low
20 acoustic impedance and low ultrasonic attenuation. The material may be a plastics material such as, for example, a cross linked polystyrene. The body 12 has a relatively complex shape with a number of faces. In the embodiment shown the body 12 takes the form of a dodecahedron having twelve differently shaped faces. The body 12 includes a transducer engagement face 16, a primary reflection face 18, a sampling face 20 and a
25 return reflection face 22.

The transducer 14 is a longitudinal wave ultrasonic transducer. In the embodiment shown, there is provided a single transducer 14 adapted to both generate and receive ultrasound. It will be appreciated that an alternative embodiment of the invention may
30 incorporate separate generation and reception transducers, and the constructional

aspects of such an embodiment will be discussed in greater detail below. An example of a transducer 14 suitable for use in connection with the present invention is shown in figure 8. The transducer 14 essentially comprises a body of piezoelectric material 42 of which opposing sides have been coated with a conductive metal film or paint to form electrodes 44,46. Upon experiencing a voltage difference across the electrodes 44,46, the body 42 changes in thickness and consequently exerts a force, in the direction indicated by arrow 48, upon any medium which the body 42 may be in contact. It will be appreciated that the illustration of figure 8 is greatly simplified and that the actual transducer 14 includes additional components such as, for example, a backing material which ensures that the force 48 exerted by the body 42 is orientated in a predetermined direction. It will further be appreciated that the transducer 14 may be configured so as to operate in reverse such that force applied to the body 42 is converted into an electrical signal representative of said force.

In describing the orientation of the aforementioned faces 16,18,20,22 to one another reference will be made to a reference plane on which a base face 24 of the body 12 lies. The reference plane is illustrated by broken line 26 on figure 5 and the broken lines 26 and 28 of figure 1. Both the transducer engagement and primary reflection faces 16,18 are perpendicular to the reference plane with the reflection face 18 being inclined relative to the transducer face 16. The inclination angle of the transducer and reflection faces 16, 18 is chosen so as to permit the propagation of ultrasonic waves within the body 12 in a predetermined fashion as will be described in greater detail below.

Looking now at the sampling and return reflection faces 20, 22, it will be noted that both of these are inclined relative to the reference plane. The sampling face 20 is inclined at a relatively shallow angle, while the return reflection face 22 is inclined at a relatively steep angle. Again the inclination of the respective faces 20, 22 is chosen so as to permit the propagation of ultrasonic waves within the body 12 in a predetermined fashion.

Operation of the apparatus 10 will now be described. Firstly, a liquid, for example oil, is brought into contact with the sampling face 20. The block 12 may, for example, be incorporated into a liquid reservoir, with the sampling face forming a portion of the reservoir wall. The transducer 14 is then operated to produce a longitudinal wave L_g directed towards the primary reflection face 18 as shown in figure 4. The wave L_g impinges on the face 18 at an angle a to the face normal 30 and produces a reflected longitudinal wave L_r and a mode converted vertically polarised shear wave SV_{mc} . The propagation direction of the reflected longitudinal wave L_r is different to that of the shear wave SV_{mc} as the two mode types have different propagation velocities. The actual directions of the reflected waves are governed by Snell's Law. The impingement angle a of the longitudinal wave L_g is selected to so as to maximise the generation of the shear wave SV_{mc} . In an exemplary embodiment the impingement angle a may be 65 degrees which results in a reflected wave L_r at the same angle to the normal 24 and a shear wave SV_{mc} reflected at an angle b of 25 degrees. It will be appreciated that the propagation direction of the shear wave is substantially parallel to the plane of the transducer engagement face 16. The reflected longitudinal wave L_r is directed towards a face 32 of the block 12 having an ultrasonic absorber layer 34 which, as its name suggests, absorbs the wave L_r .

Looking now to figure 5, there is shown the subsequent path of the shear wave. It will be appreciated that the view of figure 5 is substantially perpendicular to the view shown in figure 4. Thus the vertically polarised shear wave of figure 4 may be considered in the view shown in figure 5 to be a horizontally polarised shear wave SH with reference to the sampling face 20 it now approaches. The shear wave SH impinges upon the sampling face 20 at a shallow angle c . In an exemplary embodiment the angle may be 80 degrees to the plane normal 36. The shallow nature of the angle c ensures that no mode conversion of the incident shear wave SH occurs at the solid/liquid boundary present at the sampling face 20. The wave, now indicated SH_r is reflected away from the sampling face 20 at the same angle and subsequently impinges perpendicularly upon the return reflection face 22. The wave SH_r is then reflected back along the same path.

Referring now to figure 6 there is shown the return path of the reflected horizontally polarised shear wave. Due to the rotation of the view the reflected wave may be considered to be a vertically polarised shear wave SVr with reference to the reflection face 18 it is now approaching. Upon impinging upon the reflection face 18, the reflected wave SVr undergoes a similar transformation to that described with reference to figure 4. A portion of the energy of the wave SVr is reflected as a vertically polarised shear wave SVrr, while the remainder mode converts into a longitudinal wave Li. The geometry of the reflection face 18 ensures that the longitudinal wave Li is directed to the transducer 14, while the shear wave SVrr is directed to a further face 38 of the body 12 provided with an acoustic absorber 40.

The reflectivity of the at the

15

20

25